

SPECIFICATIONS

- Handle:** Metal, BROEN-LAB POLYCOAT powder coated with media indication according to EN13792
- Hose nozzle:** Removable plastic
- Headwork:** Diaphragm type
- Opening/closing function:** 1 1/2 x 360°
- Temperature range:** 0-65°C
- Max. working pressure:** 10 bar / 147 psi
- Test pressure:** 1 x working pressure
- Weight:** 0.7 kg

MATERIALS WITH MEDIA CONTACT

- Diaphragm:** PTFE
- Plastics:** PVDF
- Rubber:** EPDM



ORDERING INFORMATION

For standard configuration please refer to the item numbers below.



- Other options:
- different sizes of push fittings
 - different inlet lengths

BROEN-LAB UNIFLEX™ FITTINGS FOR SPECIAL WATER

Model: With R3/8 push fitting

Media	S = 150mm	S = 200mm
 Distilled water	2533 046 1003-09	2533 033 1003-09
 Deionized water, cold	2533 046 1036-09	2533 033 1036-09

Model: Without push fitting

Media	S = 150mm	S = 200mm
 Distilled water	2533 008 1003-09	2533 010 1003-09
 Deionized water, cold	2533 008 1036-09	2533 010 1036-09

For further information and mounting instructions please refer to www.BROEN-LAB.com or contact your local BROEN-LAB representative.